

## Fox ESS SMART LAN SMART L 3.0



### Easy Installation

plug and  
play installation.



### Strong Signal

Strong LAN signal  
for maximum range.



### IP65 Rated

Suitable for  
outdoor installation.



### Remote Monitoring

Connect to the  
Fox ESS Cloud.

The Smart L3.0 is an intelligent LAN enabled device allowing you to monitor the status and performance of your Fox ESS PV system via the Fox ESS Cloud remote monitoring platform. The Smart L3.0 is ideal in situations where there is no reliable WiFi or GPRS connection available.

System owners and installers can easily keep up-to-date with performance data in real-time, view historic records and monitor system alerts.

- Stable lan communication
- IP65 protection class
- Vodafone, Tata, Aircel and Airtel compatible
- Clean and compact design
- User-friendly monitoring app
- Plug and play installation
- Monitor your system from anywhere
- 24/7 monitoring



# Fox ESS SMART LAN

## SMART L 3.0

### SPECIFICATIONS

Product model	Smart L 3.0
Dimensions (L*W*H) [mm]	100.0*49.0*28.0
Weight [g]	55
Input Voltage [V]	DC7 ~ 12
Max. Power [W]	1
Ethernet Speed [M]	10/100
Interface	RS485
Parameter	9600/8/n/1(default)
Green LED	Receive Data from Inverter
Red LED	Work status
connector	USB
Temperature	-20 ~ 60
Humidity [%]	0 ~ 95 (no condensation)
Altitude [M]	≤4000
Ingress Protection	IP65
Fire rating	UL94V-0
UV immunity	F1

