

# Fox ESS ECS BATTERY STORAGE SYSTEM



## HIGH VOLTAGE BATTERY FROM Fox ESS

The ECS is a high-performance, scalable battery storage system. The modular design allows for maximum flexibility, making it suitable for a broad range of storage applications.

Additional batteries can be installed in series, allowing for a maximum storage capacity of 19.35 kWh. Installation is easy, with a plug and play solution that can save valuable time for installers.

- 2.76kWh capacity
- Scalable to 19.35 kWh
- 90% Depth of Discharge
- Large temperature tolerance
- Easy installation
- CAN/RS485 communication
- High voltage



High Voltage



Simple  
Installation



Height  
Efficiency



Expandable  
System



90%  
DoD

MODEL	ECS2800 -H2	ECS2800 -H3	ECS2800 -H4	ECS2800 -H5	ECS2800 -H6	ECS2800 -H7
ELECTRICAL CHARACTERISTICS						
Battery Type	LiFePO4 Prismatic Cell					
Battery Module	1*CM2800 1*CS2800	1*CM2800 2*CS2800	1*CM2800 3*CS2800	1*CM2800 4*CS2800	1*CM2800 5*CS2800	1*CM2800 6*CS2800
Nominal Capacity[Wh]	5530	8290	11060	13820	16590	19350
Nominal Voltage [V]	115.2	172.8	230.4	288	345.6	403.2
Operating Voltage[V]	104.4 ~ 132.4	156.6 ~ 198.7	208.8 ~ 264.9	261.0 ~ 331.2	313.2 ~ 397.4	365.4 ~ 463.6
Recommend Discharge Current [A]	24					
Max.Charge/Discharge Current [A]	48					
Peak Discharge Current [A]	65 @60sec					
Battery Pack Round-Trip Efficiency [%]	>95					
Depth of discharge [%]	90					
Cycle Life*1	≥6000					
Communication	CAN					
Display	CS: LED*1, CM: LED*6					
Scalability	Max. 7 Modules in Series					
OPERATING CONDITIONS						
Installation Location	Outdoor/ Indoor (Stand)					
Operating Temperature [°C]*2	Charge: 0 ~ 55 Discharge: -10 ~ 55					
Storage Temperature [°C]	-20 ~ 55					
Cooling method	Natural Convection					
Humidity [%]	5 ~ 95 (No Condensing)					
Altitude [m]	Max. 2,000					
MECHANICAL CHARACTERISTICS						
Dimensions (W*H*D) [mm]	570*350*380	570*470*380	570*590*380	570*710*380	570*830*380	570*950*380
Weight [kg]	65±1	95.5±1.5	126±2	157±2.5	187±3	217±3.5
CERTIFICATES						
Safety	IEC 62619					
EMC	IEC 61000-6-1/2/3/4					
Transportation	UN38.3					
Ingress Protection	IP65					

\*1, 25°C, @90% DOD, 0.5C charging/discharging.

\*2, Charge derating will occur between 0°C and +15°C.

